

GENERATOR MODEL		HNCMS50D	
	Generator Specifications	PRP	ESP
	Power	kW/kVA	50 /62    56 /70
	Rated Speed	r.p.m.	1500/1800
	Available Voltages	V	220~440
	Frequency	Hz	50/60
	Phase		3-PH
	Power Factor	CosØ	0.8
	Fuel Cons 100%	L/H	11.2
	Auxiliary Voltage	DC	24V
	Number Of Batteries		2



**Emergency standby Power (ESP):**

Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.

**Prime Power (PRP):**

Applicable for supplying power to varying electrical load for unlimited hours. PrimePower (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.

**Continuous Power (COP):**

Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.


**HAONENG generators are CE certified and conform to the following Directives:**

EN 12100:2010, EN ISO 8528-13: 2016, EN 60204-1: 2018, EN 61000-6-2:2019, 2006/42/CE Machinery safety  
2014/35/EU Low voltage  
2014/30/EU Electromagnetic compatibility • Power according to ISO 8528 and ISO 3046 • Ambient reference conditions 1000 mbar, 25°C, 30% relative humidity. Information based on standard specification equipment unless otherwise stated.

FREQUENCY   
 DIESEL FUEL   
 WATER-COOLED   
 SOUNDPROOF   
 CERTIFICATION   
 ISO 9001   
 STACKABLE

DIMENSION		OPEN TYPE	SILENT TYPE
	Length (L)	mm	1750    2400
	Width (W)	mm	900    1000
	Height (H)	mm	1250    1300
	Dry Weight	Kg	870    1500
	Fuel Tank	L	OPTION    OPTION

## Dimension and Weight



Weights and dimensions based on standard products. Technical data described in this catalogue correspond to the available information at the moment of printing. The illustrations and images are indicative and may not coincide in their entirety with the product. Industrial design under patent.



## Engine Specifications

ENGINE	CUMMINS
Engine Model	4BTA3.9-G2
Number Of Cylinders	Four
Cylinder Arrangement	In-Line
Cycle	Four Stroke
Bore x Stroke	102 × 120 mm
Displacement	3.9 L
Voltage Frequency	50/60HZ
Prime Power/Speed	62 /1500 [kva/rpm]
Standby Power/Speed	68 /1500 [kva/rpm]

ENGINE	CUMMINS
Air Intake Mode	Turbocharged
Speed Governor	Electronic Speed Regulation
Start Type	Electrical
Compression Ratio	16.5:1
Speed Stability (%)	≤3%
Consumption @ 100% load PRP	11.2 L/H
Emission	GB 20891-2014 Stage II
Coolong System (Open Type)	50°C Tropical Radiator
Coolong System (Silent Type)	50°C Tropical Radiator

## Alternator Specifications

ALTERNATOR	
Alternator Brand	Stanford
Rated Voltage	220V/440V
Voltage Frequency	50/60HZ
Exciter Type	Brushless, Single bearing
Excitation System	AVR
Winding Structure	2/3 pitch

ALTERNATOR	
Insulation Grade	H
Protection Grade	IP22
Power Factor	0.8
Stable Voltage Regulation Rate	≤ ±1%
Transient Voltage Regulation	≤ -18% ~ +20%
Voltage Waveform Distortion rate	THD ≤ 3%



## Controller Brands

